

DSP108 DSP208 DSP308 DSP408

Outdoor Column Speaker



Description

This outdoor column speaker, certified with a waterproof rating and featuring an aluminum mesh cover to prevent corrosion, is equipped with speaker units renowned for their high sensitivity and wide dynamic range. It also incorporates a dual-crossover design to deliver superior sound quality in outdoor environments.

Features


- The products have gotten waterproof certificate and other certificates and are suitable for outdoor use.
- The net cover is made of aluminum and would not rot.
- The speaker units have the features of high sensitivity and high dynamic range.
- The speaker is the construction of dual-crossover.

Specifications

| | | • | | | |
|-----------------------|------|---------------|---------------|---------------|---------------|
| Model | | DSP108 | DSP208 | DSP308 | DSP408 |
| Frequency Response | | 140Hz-14kHz | 140Hz-14kHz | 140Hz-14kHz | 140Hz-14kHz |
| Sensitivity | | 87±2dB | 89±2dB | 91±2dB | 93±2dB |
| MAX. SPL. | | 97±2dB | 102±2dB | 106±2dB | 109±2dB |
| Rated Power | | 10W | 20W | 30W | 40W |
| Rated | 70V | 5W-10W | 10W-20W | 15W-30W | 20W-40W |
| Voltage | 100V | 10W | 20W | 30W | 40W |
| Dimensions (L×W×H) | | 125×150×310mm | 125×150×410mm | 125×150×500mm | 125×150×620mm |
| Weight | | 2.3kg | 3.3kg | 4.4kg | 5.5kg |

Frequency Response

(dB SPL, 1W, 1m)



Distortion (THD<1.5% 1W, 1m, 200Hz-10kHz)

